



** NOTE: The TAZ Sail Numbers are derived from digital 8 numbers from which any number from 0-9 can be obtained. Ten digital 8 numbers are supplied.*

RACE SAIL NUMBERS

If you are applying the self-adhesive numbers to the sail you should do this before you sail your boat for the first time. The sail numbers are exclusive to the boat and correspond with the serial number/ sail number plate. Follow these instructions carefully - it is not a job to be hurried.

1:1 Lay the sail out on a large flat, clean surface with the luff sleeve to your right and the leech to your left. You should align the top starboard numbers 50mm below the lowest batten as pictured. The ISAF Rules specify that the numbers shall be at different heights on the two sides of the sail - those on the port side being the lower.

1:2 Starting on the starboard side. The left hand edge of the first digit of your sail number should be positioned 50mm in from the dacron sailcloth on the leech of the sail and the top edge 50mm below and running parallel with the lowest batten as pictured. You should apply this first.

1:3 Carefully peel away about one centimetre of the backing paper from the foot of the number and press the exposed portion down on to the pencilled base line. Work upwards, carefully pressing down the number while peeling away the backing paper making sure there are no bubbles or wrinkles. Finally, rub the number down very hard all over.

Carry on with the other digits leaving a minimum 30mm space between each one.

1:4 When you have completed the full number on the starboard side, turn the sail over and apply the port side numbers 30mm below the starboard side row of numbers.

1:5 Starting in line with the starboard numbers and working from the right to left, apply the port numbers as before.

1:6 The MYLAR of the RACE SAIL is highly adhesive so there is no need to use an iron to permanently fuse the numbers on to the sailcloth.

To permanently fuse the numbers on to STANDARD DACRON sailcloth, gently iron on the reverse side of the numbers with a warm iron. Do not use an iron directly on the numbers.

